



CHASSIS™ Plank and Tile


Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	7" x 48" / 177.8mm x 1219.2mm (Plank) 18" x 18" / 457.2mm x 457.2mm (Tile)	
Overall Thickness*	.080" / 2.0mm	
Wear Layer	6 mil / 0.15mm, featuring ruff Shield finish	
Edge	Square	
Standard Colors	4 standard planks / 2 standard tiles	
Installation Method	Glue Down	
Wear Limited Warranty	20 Year Residential / 10-Year Light Commercial	
Recycled Content	This product contains 50% recycled content. 100% recyclable post-use	
Packaging	PLANK 32.72 ft ² (3.04 m ²) per carton 14 pieces per carton 85 cartons per pallet 18 pallets per 20' container	TILE 35.95 ft ² (3.34 m ²) per carton 16 pieces per carton 76 cartons per pallet 18 pallets per 20' container
Weight Per Carton	24.00 lbs / 10.87 kg	26.43 lbs / 11.99 kg



Shepherd-CHA 7484

Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




Motorcoach CHA 7481



Suspension CHA 7482



Farnham CHA 7483



Shepherd CHA 7484



Veridian CHA 7485



Calais CHA 7486

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.