



Reposado™ Plus

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" (nom)
Overall Thickness*	3.5 mm (2.5 mm + 1 mm cushion backing)
Wear Layer	12 mil featuring uff Shield finish
Edge	Square
Standard Colors	4 colors
Installation Method	Glue-Down
Wear Limited Warranty	30-Year Residential / 20-Year Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use.
Packaging	32.67 ft ² (3.04 m ²) per carton 14 pieces per carton 60 cartons per pallet
Weight Per Carton	34.87 lbs / 15.82 kg



Sunrise RPD-732CB

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
+STC Sound Testing	ASTM E 90 / E 413	+STC 62
+IIC Sound Testing	ASTM E 492 / E 989	+IIC 72




BEST WEAR LIMITED WARRANTY

SCS Certified



Paloma RPD-731CB



Matador RPD-733CB



Sunrise RPD-732CB



Siesta RPD-734CB

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.stcfloors.com for full product and warranty details.