

EW-48U Data Sheet

EarthWerks Acoustical Underlayment for Luxury Vinyl Tile (LVT)

EarthWerks LVT Flooring Underlayment is a Premium Grade highly engineered, cross-linked polypropylene foam. EarthWerks LVT is the ideal choice for most residential and commercial Luxury Vinyl Tile (LVT) flooring applications.

- The highest rated and most effective acoustic barrier on the market. Provides unsurpassed through the floor and footfall noise reduction.
- Proprietary Advanced Cell Technology™
The most robust compression characteristics on the market help to insure the integrity of the tongues and grooves.
- Light, strong and flexible –making it easy to handle and install in nearly all conditions.
- Mold and mildew resistant.
- Exceeds the (40) psi ASTM test standard for compressive strength required for LVT flooring installations
- Resilient, nonreactive and fully recyclable making it an environmentally friendly option
- Surpasses the Indoor Air Quality emissions requirement for California’s Section 01350 -the most stringent volatile organic compound (VOC) emissions standard in North America

Product and Packaging Specifications:

IIC	*69 dB
STC	*66 dB
MVTR	.3 lbs/1000ft ² /24 hrs
R Value	3 ft ² -F-hr/BTU-in
Roll Dimension	35" x 51.4'
Rolls Per Carton	12
Rolls per pallet	120
Pallets per TL	26

*will vary depending on specific floor/ceiling assembly



For more information about EW LVT Underlayment Adhesive System or any of our other flooring underlayment products, please contact us 1-800-275-7943 or at www.earthwerks.com