

Aurora

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	8" x 39.5" / 200mm x 1000mm
Overall Thickness*	3/16" / 4.5mm
Wearlayer	20 mil / 0.50mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities.
Construction	Layered plank consisting of wearlayer, film and backing.
Edge	Square
Standard Colors	8" x 39.5": 8 standard colors
Installation Method	Loose-Lay
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains a minimum 50% recycled content. 100% recyclable post-use.
Packaging	8" x 39.5": 25.83 ft ² (2.40 m ²) per carton 12 pieces per carton 50 cartons per pallet 20 pallets per 20' container
Weight Per Carton	38.28lbs / 17.36kg

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and application recommendations.

