

Avante Groutable Tile

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	16" x 16" / 406.4 mm x 406.4 mm 12" x 24" / 304.8 mm x 609.6 mm	
Overall Thickness*	1/8" / 3.0mm	
Wearlayer	8 mil / .2mm - Also features our Infinity Shield™ finish technology for superior scratch and stain resistance qualities.	
Construction	Layered tile consisting of wearlayer, film and backing.	
Edge	4-side Rounded	
Standard Colors	16" x 16": 12 standard colors 12" x 24": 6 standard colors	
Installation Method	Glue Down - Use with or without grout.	
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial	
Recycled Content	This product contains no recycled content. 100% recyclable post-use.	
Packaging	16" x 16" 28.44 ft ² (2.64 m ²) per carton 16 pieces per carton 48 cartons per pallet 24 pallets per 20' container	12" x 24" 32 ft ² (2.97 m ²) per carton 16 pieces per carton 52 cartons per pallet 20 pallets per 20' container
Weight Per Carton	34.89 lbs / 15.83 kg	39 lbs / 17.69 kg
Product Testing		
Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

ST-100 adhesive recommended for this product. For other approved adhesives, please contact your local authorized dealer. Installed with or without grout. Recommended LVT Grout colors include: Biscuit, Chamois, Gray, & Ivory.

