

Cambridge

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	6" x 36" / 152.4mm x 914.4mm	
Overall Thickness*	.080" / 2.0mm	
Wearlayer	12 mil / 0.30mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities.	
Construction	Layered plank consisting of wearlayer, film and backing.	
Edge	Square	
Standard Colors	6" x 36": 6 standard colors	
Installation Method	Glue Down	
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial	
Recycled Content	This product contains a minimum 50% recycled content. 100% recyclable post-use.	
Packaging	6" x 36": 27 ft ² (2.51 m ²) per carton 18 pieces per carton 108 cartons per pallet 18 pallets per 20' container	
Weight Per Carton	20.95lbs / 9.5kg	
Product Testing		
Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

