

Dunbar™

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	5" x 48" / 127mm x 1219.2mm
Overall Thickness*	1/6" / 4.0mm
Wearlayer	20 mil / 0.50mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities.
Construction	Layered plank consisting of wearlayer, film and backing.
Edge	Beveled Edge
Standard Colors	4 standard colors
Installation Method	Glue Down
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial Wear Limited Warranty
Recycled Content	This product contains no recycled content. 100% recyclable post-use.
Packaging	5" x 48" 20 ft ² (1.86 m ²) per carton 12 pieces per carton 70 cartons per pallet 17 pallets per 20' container
Weight Per Carton	29.10lbs / 13.23kg

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

