

Hathaway

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile

Size* 6" x 48" / 153mm x 1220mm

Overall Thickness* 1/8"/ 3.0mm

20 mil / 0.50mm - Also features our **duff Shield** finish technology Wearlayer

for superior scratch and stain resistance qualities.

Construction Layered plank consisting of wearlayer, film and backing.

Beveled Edge

Standard Colors 6" x 48": 6 standard colors

Glue Down Installation Method

Lifetime Residential / 30-Year Commercial **Wear Limited Warranty**

This product contains a minimum 50% recycled content.100% recyclable post-use. **Recycled Content**

6" x 48": **Packaging**

35.95 ft² (3.34 m²) per carton

18 pieces per carton 60 cartons per pallet

16 pallets per 20' container

Weight Per Carton 38.13lbs / 17.33kg

Product Testing

Chemical Resistance ASTM F 925 Passed

Critical Radiant Flux Class I, CRF ≥0.45 ASTM E 648-06

Dimensional Stability Passed **ASTM F 2199** Flexibility ASTM F 137 Passed Resistance to Heat **ASTM F 1514** Passed Resistance to Light **ASTM F 1515** Passed Static Load Limit ASTM F 970 Passed Thickness ASTM F 386 Passed



*All measurements are nominal.

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.



WEARLAYER QUALITIES

Also features our Infinity Shield™ finish technology for superior scratch and stain resistance qualities.

12 mil / 0.3 mm Also features our **duff Shield** finish technology for superior scratch and stain resistance qualities.

Protected by urethane coating (PU)

PVC

WEARLAYER QUALITIES

This product contains 38% recycled content.100% recyclable post-use.

This product contains no recycled content. 50% recyclable post-use.

This product contains no recycled content.100% recyclable post-use.

WARRANTY

BETTER

20-Year Residential / 10-Year Light Commercial

BEST

30-Year Residential / 20-Year Light Commercial

PREMIUM

Lifetime Residential/ 30-Year Commercial