

Impressions

| | | |
|------------------------------|---|--------------------|
| Classification | ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile | |
| Size* | 18" x 18" / 457.2mm x 457.2mm | |
| Overall Thickness* | 1/8" / 3.0mm | |
| Wearlayer | 22 mil / 0.55mm - Protected by urethane coating (PU) | |
| Construction | Layered tile consisting of wearlayer, film and backing. | |
| Edge | Square | |
| Standard Colors | 18" x 18": 6 standard colors | |
| Installation Method | Glue Down | |
| Wear Limited Warranty | Lifetime Residential / 30-Year Commercial | |
| Recycled Content | This product contains 38% recycled content. 100% recyclable post-use. | |
| Packaging | 18" x 18": 36 ft ² (3.34 m ²) per carton 16 pieces per carton 52 cartons per pallet 20 pallets per 20' container | |
| Weight Per Carton | 39.68lbs / 18kg | |
| Product Testing | | |
| Chemical Resistance | ASTM F 925 | Passed |
| Critical Radiant Flux | ASTM E 648-06 | Class I, CRF ≥0.45 |
| Dimensional Stability | ASTM F 2199 | Passed |
| Flexibility | ASTM F 137 | Passed |
| Resistance to Heat | ASTM F 1514 | Passed |
| Resistance to Light | ASTM F 1515 | Passed |
| Smoke Density | ASTM E 662-06 | Passed |
| Static Load Limit | ASTM F 970 | Passed |
| Thickness | ASTM F 386 | Passed |



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

