

# Lancaster Plank

<b>Classification</b>	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
<b>Size*</b>	6" x 36" / 152.4mm x 914.4mm
<b>Overall Thickness*</b>	.080" / 2.0mm
<b>Wearlayer</b>	8 mil / .2mm
<b>Construction</b>	Layered plank consisting of wearlayer, film and backing.
<b>Edge</b>	Square
<b>Standard Colors</b>	6 standard colors
<b>Installation Method</b>	Glue Down
<b>Wear Limited Warranty</b>	20-Year Residential / 10-Year Light Commercial
<b>Recycled Content</b>	This product contains a minimum 50% recycled content. 100% recyclable post-use.
<b>Packaging</b>	27 ft <sup>2</sup> (2.51 m <sup>2</sup> ) per carton 18 pieces per carton 108 cartons per pallet 18 pallets per 20' container
<b>Weight Per Carton</b>	20.94 lbs / 9.5 kg

## Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



**\*All measurements are nominal.**

*Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and adhesive/application recommendations.*

