

Rapid Clic

| | |
|------------------------------|--|
| Classification | ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile |
| Size* | 7" x 48" / 177.8mm x 1219.2mm |
| Overall Thickness* | 1/5" / 5.0mm |
| Wearlayer | 20 mil / 0.50mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities. |
| Construction | Layered plank consisting of wearlayer, film and backing. |
| Edge | 4-sided Bevel |
| Standard Colors | 7" x 48": 10 standard colors |
| Installation Method | Click floating utilizing unilin locking system. |
| Wear Limited Warranty | Lifetime Residential / 30-Year Commercial |
| Recycled Content | This product contains no recycled content. 100% recyclable post-use. |
| Packaging | 7" x 48": 17.88 ft ² (1.66 m ²) per carton 8 pieces per carton 70 cartons per pallet 16 pallets per 20' container |
| Weight Per Carton | 33.9lbs / 15.38kg |

Product Testing

| | | |
|-----------------------|---------------|--------------------|
| Chemical Resistance | ASTM F 925 | Passed |
| Critical Radiant Flux | ASTM E 648-06 | Class I, CRF ≥0.45 |
| Dimensional Stability | ASTM F 2199 | Passed |
| Flexibility | ASTM F 137 | Passed |
| Resistance to Light | ASTM F 1515 | Passed |
| Smoke Density | ASTM E 662-06 | Passed |
| Static Load Limit | ASTM F 970 | Passed |
| Thickness | ASTM F 386 | Passed |



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

