

Runway™

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	4" x 36" / 101.6mm x 914.4mm
Overall Thickness*	.080" / 2.0mm
Wearlayer	12 mil / 0.30mm - Also features our Tuff Shield finish technology for superior scratch and stain resistance qualities.
Construction	Layered plank consisting of wearlayer, film and backing.
Edge	Square Edge
Standard Colors	6 standard colors
Installation Method	Glue Down
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use.
Packaging	4" x 36" 24 ft ² (2.23 m ²) per carton 24 pieces per carton 99 cartons per pallet 20 pallets per 20' container
Weight Per Carton	19.40lbs / 8.79kg

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



***All measurements are nominal.**

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

