



Technical Data - CANTO Planks


Gala, Lava, Rio

CANTO Planks is a high level LVT-Flooring for residential and light commercial use.

Gala: 2 Décors - Lava: 8 Décors - Rio: 10 Décors

Characteristic	Norm	Data
Type of flooring	EN 649	Heterogen, PVC
Surface treatment		PU
Size	EN 427	Gala, Rio: 19,20 x 123 cm / Lava: 17,80 x 121,98 cm
Total thickness	EN 428	2,0 mm
Wearlayer thickness	EN 429	0,30 mm
Beveled edges		No
Performance classification	EN 685	23, 31
Weight per m ² (approx.)	EN 430	Gala, Rio: 3,9 kg / Lava: 3,8 kg
Number of pieces per carton		Gala, Rio 12 = 2,83 m ² / Lava 12 = 2,60 m ²
Wear group	EN 660-2	Group T
Residual indentation	EN 433	Conforms
Fire	EN 13501-1	Bfl- S1
Reduction transmission impact noise	EN 140-8	2 dB
Color fastness	ISO 105-B02	≥6
Anti-slip classification	DIN 51130	R 10
Resistance to chemicals	EN 423	Unchanged *
Suitable for floor heating		Yes
Castor chair suitability	EN 425	Yes (Type W)
Emissionen AgBB Z 156.603-1194		Conforms
DoP (Declaration of performance)		052311299
Cleaning and maintenance		CC-Dr. Schutz (or similar)

* during brief exposure to regular household products



04.08.2015

