




Technical Data - COMBO Planks

OP Planks

COMBO OP Planks is a high level LVT-Flooring (planks in 47 Decors) for residential and contract use.

Characteristic	Norm	Data
Type of flooring	EN 649	Heterogen, PVC
Surface treatment		PU
Size	EN 427	Tempo 22,86 x 121,92 cm GWC 18,40 x 95 cm / Others 17,78 x 121,92 cm
Total thickness	EN 428	GWC 3,0 mm / Others 2,5 mm
Wearlayer thickness	EN 429	GWC 0,50mm / Others 0,55 mm
Beveled edges		Tempo: Yes / Others: No beveled edges
Performance classification	EN 685	23, 33, 42 (GWC: 23,32,41)
Weight per m ² (approx.)	EN 430	Tempo: 4,6 kg / GWC: 4,8 kg / Others: 4,7 kg
Number of pieces per carton		Tempo 12 = 3,34 m ² / GWC 19 = 3,32 m ² Others 18 = 3,90 m ²
Wear group	EN 660-2	Group T
Residual indentation	EN 433	Conforms
Fire	EN 13501-1	Bfl- S1
Reduction transmission impact noise	EN 140-8	5 dB
Color fastness	ISO 105-B02	≥6
Anti-slip classification	DIN 51130	GWC, OP9914, OP9931: R9 Others: R10
Resistance to chemicals	EN 423	Unchanged *
Suitable for floor heating		Yes
Castor chair suitability	EN 425	Yes (Type W)
Emissionen AgBB Z 156.603-1194		Conforms
DoP (Declaration of performance)		052310214
Cleaning and maintenance		CC-Dr. Schutz (or similar)

* during brief exposure to regular household products



16.10.2015