




## Technical Data

## Jupiter

Jupiter is a high level LVT-Flooring (6 planks and 4 tiles)  
for residential and contract use - Loose Lay system.

Characteristic	Norm	Data
Type of flooring	EN 649	Heterogen, PVC
Surface treatment		PU
Size	EN 427	Planks 25 x 105 cm / Tiles 50 x 50 cm
Total thickness	EN 428	4,5 mm
Wearlayer thickness	EN 429	0,55 mm
Beveled edges		No
Performance classification	EN 685	23, 33, 42
Weight per m <sup>2</sup> (approx.)	EN 430	7,4 kg
Number of pieces per carton		Planks 12 = 3,15 m <sup>2</sup> / Tiles 12 = 3 m <sup>2</sup>
Wear group	EN 660-2	Group T
Residual indentation	EN 433	Conforms
Fire	EN 13501-1	Bfl- S1
Reduction transmission impact noise	EN 140-8	9 dB
Color fastness	ISO 105-B02	≥6
Anti-slip classification	DIN 51130	<b>R 10</b>
Resistance to chemicals	EN 423	Unchanged *
Suitable for floor heating		Yes
Castor chair suitability	EN 425	Yes (Type W)
Emissionen AgBB Z 156.603-1194		Conforms
DoP (Declaration of performance)		052410214
Cleaning and maintenance		CC-Dr. Schutz (or similar)

\* during brief exposure to regular household products



04.08.2015

