



Technical Data

Rio Clic 05

Rio Clic 05 (before Tempo Clic) is a high level LVT-Flooring (planks in 10 colours) for residential and contract use - clic floating system.

Eigenschaft	Norm	Werte
Type of flooring	EN 649	Heterogen, PVC
Surface treatment		PU
Size	EN 427	18,40 x 122 cm
Total thickness	EN 428	4,0 mm
Wearlayer thickness	EN 429	0,50 mm
Beveled edges		Yes
Performance classification	EN 685	23, 32, 41
Weight per m ² (approx.)	EN 430	7,2 kg
Number of pieces per carton		10 = 2,24 m ²
Wear group	EN 660-2	Group T
Residual indentation	EN 433	Conforms
Fire	EN 13501-1	Bfl- S1
Reduction transmission impact noise	EN 140-8	7 dB
Color fastness	ISO 105-B02	≥6
Anti-slip classification	DIN 51130	R 10
Resistance to chemicals	EN 423	Unchanged *
Suitable for floor heating		Yes
Castor chair suitability	EN 425	Yes (Type W)
Emissionen AgBB Z 156.603-1194		Conforms
DoP (Declaration of performance)		052311040
Cleaning and maintenance		CC-Dr. Schutz (or similar)

* during brief exposure to regular household products



04.08.2015