



# WOOD CLASSIC II

## WOOD CLASSIC II XL

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile	
Size*	8" x 48" / 203.20mm x 1219.20mm	
	9.5" x 60" / 241.30mm x 1524mm (XL)	
Overall Thickness*	0.12" / 3.0mm	
Wear Layer	20 mil / 0.5mm, featuring <b>Tuff Shield</b> finish	
Edge	Micro Beveled	
Standard Colors	8 standard planks / 4 standard planks (XL)	
Installation Method	Glue Down	
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial	
Recycled Content	This product contains no recycled content. 100% recyclable post-use	
Packaging	<b>PLANK</b> 32.00 ft <sup>2</sup> (2.97 m <sup>2</sup> ) per carton 12 pieces per carton 48 cartons per pallet 20 pallets per 20' container	<b>PLANK (XL)</b> 31.52 ft <sup>2</sup> (2.93 m <sup>2</sup> ) per carton 8 pieces per carton 72 cartons per pallet 14 pallets per 20' container
Weight Per Carton	36.72 lbs / 16.66 kg	35.08 lbs / 15.91 kg



London Oak-WCT 9201


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




London Oak WCT 9201 (EIR)



York Oak WCT 9203 (EIR)



Oslo Oak WCT-9205 (EIR)



Toronto Oak WCT 9207 (EIR)



Driftwood WCT 9209 XL (EIR)



Timberlake WCT 9211 XL (EIR)



Berlin Oak WCT 9202 (EIR)



Paris Oak WCT 9204 (EIR)



California Oak WCT 9206 (EIR)



Alaska Oak WCT 9208 (EIR)



Berkshire WCT 9210 XL (EIR)



Torres WCT 9212 XL (EIR)

\*All measurements are nominal.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.