

## Portia™

<b>Classification</b>	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
<b>Size*</b>	7" x 48" / 177.8mm x 1219.2mm
<b>Overall Thickness*</b>	1/8" / 3.0mm
<b>Wearlayer</b>	20 mil / 0.50mm - Also features our <b>Tuff Shield</b> finish technology for superior scratch and stain resistance qualities.
<b>Construction</b>	Layered plank consisting of wearlayer, film and backing.
<b>Edge</b>	Beveled Edge
<b>Standard Colors</b>	6 standard colors
<b>Installation Method</b>	Glue Down
<b>Wear Limited Warranty</b>	Lifetime Residential / 30-Year Commercial
<b>Recycled Content</b>	This product contains a minimum of 50% recycled content. Product can be fully recycled post-use.
<b>Packaging</b>	7" x 48" 34.98 ft <sup>2</sup> (3.25 m <sup>2</sup> ) per carton 15 pieces per carton 60 cartons per pallet 16 pallets per 20' container
<b>Weight Per Carton</b>	37.48lbs / 17kg

### Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



**\*All measurements are nominal.**

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and adhesive/application recommendations.

