



# REVEILLE PLUS XL


Solid Polymer Core Flooring




Debonair  
BRV-350CB




Repose  
BRV-351CB




Suitable  
BRV-352CB



Sanderling  
BRV-353CB



Ethereal  
BRV-354CB



Umber  
BRV-355CB

<b>CLASSIFICATION</b>	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
<b>SIZE</b>	9" x 60" / 230 mm x 1524 mm (nom)
<b>OVERALL THICKNESS</b>	0.20" / 5.0 mm (4 mm + 1 mm cushion backing)
<b>WEAR LAYER</b>	20 mil / 0.50 mm featuring Superior Coating finish
<b>CONSTRUCTION</b>	ABA SPC
<b>EDGE</b>	Bevel
<b>STANDARD COLORS</b>	6 colors
<b>INSTALLATION METHOD</b>	Angle/Angle
<b>WEAR LIMITED WARRANTY</b>	30 Year Residential / 15 Year Commercial
<b>RECYCLED CONTENT</b>	This product contains no recycled content. 100% recyclable post-use.

<b>PACKAGING</b>	30.18 ft <sup>2</sup> (2.80 m <sup>2</sup> ) per carton 8 pieces per carton 56 cartons per pallet
<b>WEIGHT PER CARTON</b>	50.99 lbs / 23.13 kg



Coordinating Moldings

## PRODUCT TESTING

Chemical Resistance	ASTM F 925	PASS	Resistance to Light	ASTM F 1515	PASS
Critical Radiant Flux	ASTM E 648-17	PASS CLASS 1	Smoke Density	ASTM E 662-15A	PASS
Dimensional Stability	ASTM F 23999	PASS	Static Load Limit	ASTM F 970	PASS
Residual Indentation	ASTM F 1914	PASS	Slip Resistance	ASTM C 1028	PASS
Resistance to Heat	ASTM F 1514	PASS	IIC Sound Testing	ASTM E 989-06	+IIC 61
			STC Sound Testing	ASTM E 413-16	+STC 53



Waterproof Low Maintenance Acoustical Attributes Durable Hygienic Pet Friendly Kid Friendly



\*All measurements are nominal. All specifications and offerings are subject to change without notice. Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.